

# COLLAGE Acoustic notice board

AKUSTIKMILJÖ // ENVIRONMENT-FRIENDLY SOUND ABSORBENTS WITH FOCUS ON FUNCTION & DESIGN



COLLAGE is the versatile adsorbent for schools, kindergartens and offices.  
Photo: Egmont use COLLAGE for editorial storyboards.

When the acoustic quality needs to be improved at the same time as the walls serve a useful purpose, COLLAGE is an excellent solution. COLLAGE combines sound function and practical properties in a brilliant way as it is also made for putting up pictures, notes and information.

## Advantage

- **The right height:** It is often we ourselves that represent the source of the noise, which is why it is important to absorb vertically at the level where we are.
- **Quality & Environment:** COLLAGE is made from EcoSUND®, a high-class sound absorbent, class A. EcoSUND consists of recycled PET-bottles and plant fibres.
- **Effective:** COLLAGE works effectively with early reflections on wall surfaces head-high, necessary as noise often originates from human speech.
- **Practical:** Combines function and practical qualities.
- **Colour:** Available in several colours to fit pre-schools as well as offices.

57%

57 percent of the teachers "often" or "sometimes" have difficulties hearing what the pupils say in the classroom.

THE SWEDISH ASSOCIATION OF HARD OF HEARING PEOPLE, THE HRF

## Fields of application



Office



Conference



School



## Size

- 600x600x50 mm
- 1200x600x50 mm
- 1200x900x50 mm
- 1200x1200x50 mm
- 1200x1600x50 mm
- 1200x2400x50 mm

## Frames

COLLAGE is as standard available with a black or a white frame. Upon request, we can also deliver other colours.

## Mounting

COLLAGE is easily mounted by being hung up on 2 or 4 screws in the pre-stamped key holes at the back of the frame or, as an alternative, with a mounting strip for tight installation or with a mounting strip providing a 50 mm air gap.


## Acoustic qualities

Carried out by SP, the National Swedish Testing Institute, according to ISO 354 and ISO 11654

Product	Surface	Construct. height	63	125	250	500	1'	2'	4'	$\alpha_w$
Collage	Trevira	50	0,05	0,30	0,60	0,95	1,0	0,95	0,85	0,90
50 mm	Trevira	100	0,10	0,35	0,75	1,0	1,0	0,90	0,90	0,95

## Colour

COLLAGE is as standard delivered in white, green, yellow, blue, red, grey or black design. You can also choose an alternative textile to laminate on the sound absorbent if your project requires a different visual expression.



## Cleaning

Clean with a dry brush/broom or with a vacuum cleaner. If very dirty, clean with cold water, a cloth and a gentle washing up, washing or cleaning detergent.



## EGMONT NORDISK FILM

Egmont is one of Scandinavia's leading media groups and if you enter their head office in Stockholm, you will find Akustikmiljö's LOD and COLLAGE absorbents.

## WHY AKUSTIKMILJÖ?

- Market leader when it comes to environment-friendly sound absorbents
- Absorption class-A on all products
- We offer a sustainable acoustic solution with environment and health in focus
- Our own production ensures an even and high quality

## Fire

With Akustikmiljö's standard surface layer, COLLAGE fulfils surface layer class 1, (B-s1,d0).

## About EcoSUND®

- **Environment-friendly:** EcoSUND is made from recycled PET-bottles and plant fibres.
- **No leaking:** EcoSUND is completely free from glue/binding agents and therefore does not give off any emissions or gas.
- **Stand up to moisture:** EcoSUND is not sensitive to damp and moisture and therefore cannot rot or mould.
- **No harmful fibres:** EcoSUND does not give off any itching or irritating fibres that may cause allergic reactions.

## Prescription

Designation for prescription:

- Akustikmiljö COLLAGE



Akustikmiljö i Falkenberg AB, Falkåsvägen 4, Box 77, 311 21 Falkenberg, Sweden  
Phone: +46 346 - 714850, Fax: +46 346 - 87988, info@akustikmiljo.se, www.akustikmiljo.se



akustikmiljö